

Type 4040 DC-S


**Bestell-Nr. 1005 0275**

Anwendungen	Bohren, Fräsen, Schleifen, Gravieren
Spanndurchmesser	45 mm
Motorart	Drehstromsynchronmotor
Drehzahlbereich	5.000 - 50.000 / 60.000* min ⁻¹
Spannung	45 V
Strom	max. 16 A
Drehmoment	max. 17 Ncm
Frequenz	83 - 833 / 1.000* Hz
Leistung	max. 1.050 W
Gewicht	1,7 kg
Lagerung	3 x Hybrid, lebensdauergeschmiert
Schutzart	IP 54
Motorschutz	PTC - 100 °C
Gebrauchslage	
Belastungsrichtung	axial + radial
Rundlauf (Kegel)	≤ 1,5 µm
Spannzangenbereich	Ø 1,0 - 6,35 mm (inkl. 1/8" + 1/4")
Werkzeugwechsel	2 Ring-Maulschlüssel (SW 10 + 13)
Kühlsystem	Kühlung durch Einspannvorrichtung
Geschützt gegen Schmutz und Kühlschmiermittel	Sperrluft 0,5 - 0,8 bar (Schlauch Ø außen 4 mm)
Gehäusematerial	Edelstahl
Umrichterempfehlung	e@syDrive® 4426, TV 4506**

*kurzzeitig

**reduzierte Leistung

Änderungen vorbehalten


**Part No. 1005 0275**

Applications	Drilling, Milling, Grinding, Engraving
Clamping diameter	45 mm
Motor system	Brushless DC motor (BLDC)
Speed range	5,000 - 50,000 / 60,000* rpm
Voltage	45 V
Current	max. 16 A
Torque	max. 17 Ncm
Frequency	83 - 833 / 1,000* Hz
Output power	max. 1,050 W
Weight	1.7 kg
Bearing system	3 x Hybrid, lifetime lubrication
Protection category	IP 54
Motor protection	PTC - 100°C
Working position	
Load direction	axial + radial
Run-out (taper)	≤ 1.5 µm
Chuck clamping range	Ø 1.0 - 6.35 mm (incl. 1/8" + 1/4")
Tool change	2 combination wrenches (10 + 13 mm)
Cooling system	Cooling via clamping bracket
Protected against dirt and cooling lubricant	Sealing air 0.5 - 0.8 bar (hose Ø outer 4 mm)
Housing material	Stainless steel
Inverter recommendation	e@syDrive® 4426, TV 4506**

*short term

**reduced output power

Subject to change without notice



INDUSTRIAL DRIVES

Sycotec GmbH & Co. KG

Wangener Strasse 78

88299 Leutkirch

Germany

Phone +49 7561 86-0

Fax +49 7561 86-371

info@sycotec.eu

www.sycotec.eu



A Sanavis Group Company