

4029



CE

Bestell-Nr. | Part No. **0674 2170**

Anwendungen	Bohren, Fräsen, Schleifen, Abrichten
Drehzahlbereich	5.000 – 60.000 min ⁻¹
Leistung	max. 250 W
Spanndurchmesser	33 mm
Motorart	3 Phasen-Asynchronmotor
Frequenz	83 – 1.000 Hz
Spannung	30 V
Strom	max. 8 A
Drehmoment	max. 4,5 Ncm
Motorschutz	–
Gewicht	0,8 kg
Lagerung	2x Hybrid, 1x Stahl, lebensd. geschm.
Rundlauf (Kegel)	≤ 1,5 µm
Spannzangenbereich	Ø 0,5 – 4,0 mm (inkl. 1/8")
Spannzangentyp	C1-8
Werkzeugwechsel	Manuell (Gabelschlüssel)
Kühlsystem	Kühlung durch Einspannvorrichtung
Schutzart	IP 54
Geschützt gegen Schmutz und Kühlschmiermittel	Sperrluft 0,5 – 0,8 bar (Schlauch Ø innen 4 mm)
Gehäusematerial	Edelstahl
Verbindungskabel	1,5 m
Umrichterempfehlung	e@syDrive® 4310 (IP00), 4320 (IP00), TV 4504, 4624

Applications	Drilling, milling, grinding, dressing
Speed range	5,000 – 60,000 rpm
Output power	max. 250 W
Clamping diameter	33 mm
Motor system	3 Phase asynchronous motor
Frequency	83 – 1,000 Hz
Voltage	30 V
Current	max. 8 A
Torque	max. 4.5 Ncm
Motor protection	–
Weight	0.8 kg
Bearing system	2 x Hybrid, 1 x Steel, lifetime lubricat.
Run-out (taper)	≤ 1.5 µm
Chuck clamping range	Ø 0.5 – 4.0 mm (incl. 1/8")
Chuck type	C1-8
Tool change	Manual (open-end wrenches)
Cooling system	Cooling via clamping bracket
Protection category	IP 54
Protected against dirt and cooling lubricant	Sealing air 0.5 – 0.8 bar (hose Ø inner 4 mm)
Housing material	Stainless steel
Connecting cable	1.5 m
Inverter recommendation	e@syDrive® 4310 (IP00), 4320 (IP00), TV 4504, 4624

Änderungen vorbehalten

Subject to change without notice

